

Crémone bidirectionnelle F7,5 à galet Ajustable en partie haute

Désignation UE N° d'article

Crémone bidirectionnelle ajustable en partie haute
Fouillot 7,5 mm, carré 7 mm
Épaisseur boîtier 12 mm. Cote d'entaillage conseillée 12 mm.

HFF	Long	D	GV	Cote A	Cote B	Cote C	Vis	UE	N° d'article
350- 550	556	155	-	-	-	-	2	10	G-20465-01-0-1
450- 700	706	200	-	-	-	-	2	10	G-20465-02-0-1
600- 850	856	250	1	-	396	-	4	10	G-20465-03-0-1
851-1100	1106	250	1	-	396	-	5	10	G-20465-22-0-1
851-1100	1106	400	1	-	546	-	4	10	G-20465-06-0-1
1101-1350	1356	250	1	-	646	-	6	10	G-20465-24-0-1
1101-1350	1356	400	1	-	546	-	5	10	G-20465-07-0-1
1101-1350	1356	400	1	-	646	-	6	10	G-20465-21-0-1
1101-1350	1356	500	1	-	646	-	6	10	G-20465-09-0-1
1351-1600	1606	500	1	-	796	-	8	10	G-20465-10-0-1
1601-1850	1856	500	2	-	796	1396	9	10	G-20465-11-0-1
1351-1600	1606	600	1	-	796	-	7	10	G-20465-12-0-1
1601-1850	1856	600	2	-	796	1396	8	10	G-20465-13-0-1
1851-2100	2106	600	2	-	796	1396	9	10	G-20465-14-0-1
1601-1850	1856	700	2	546	1396	-	8	10	G-20465-15-0-1
1851-2100	2106	700	2	546	1396	-	9	10	G-20465-16-0-1
1851-2100	2106	800	2	596	1396	-	9	10	G-20465-18-0-1
2101-2350	2356	800	2	596	1396	-	10	10	G-20465-23-0-1
1851-2100	2106	980	2	596	1396	-	9	10	G-20465-19-0-1
2101-2350	2356	980	2	596	1396	-	10	10	G-20465-20-0-1

Guide de tringle 100 E-13609-00-0-1

Guide de tringle
E-13609-00-0-1

